



HOT HEX – Model 23A

## List of used materials and standard parts

### Mild Steel plates

S235JRG2 □ Thickness: #1, #2, #3, #5mm \* EN 10025 : 2004  
P265GH □ Thickness: #4, #12mm \* EN 10025 : 2004

### INOX plates and bars

X6Cr17 □ Thickness: #2, #8mm \* EN 10088-2  
X5CrNi18-10 □ Diameter: Ø8, Ø12mm \* EN 10088-2

### Bronze bar

CuSn10Pb10-C(GS) □ Diameter: Ø12mm \* EN 1982 : 2008

Vermiculite [www.thermax.eu](http://www.thermax.eu) \* [www.skamol.com](http://www.skamol.com)

 **TechnoPhysik Group** **THERMAX® SF750** □ Thickness: 30mm



**SkamoStove Board 700** □ Thickness: 30mm

Glass [www.schott.com](http://www.schott.com)



**ROBAX® Glaskeramik** □ Artikel: 1526343

Ropes [www.culimeta.de](http://www.culimeta.de)



FD3506WC (door) □ FD5090 (glass) □ FB3102WAC (ash holder / air directors)

Thermoresistant paint [www.rembrandtin.com](http://www.rembrandtin.com)



□ Thermodur 600ASS HSR

**Rubberized adjustable brackets** (M12 – 6 Pieces)

**Screws-Washers-Nuts**

**Bearings** (6000ZZ - 1 Piece / 51101 – 1 Piece)